

Model			LV2MCI-09
Power supply		V-ph-Hz	220~240-1-50
Cooling	Capacity	Btu/h	9000
	Input	W	40
	Rated current	A	0,18
Heating	Capacity	Btu/h	10000
	Input	W	40
	Rated current	A	0,18
Indoor fan motor	Model		WZDK37-38G
	Qty		1
	Output	w	37(Output)
	Capacitor	uF	/
	Speed(hi/mi/lo)	r/min	730/620/560/480
Indoor coil	a.Number of rows		1
	b.Tube pitch(a)x row pitch(b)	mm	21x13.37
	c.Fin spacing	mm	1,3
	d.Fin type (code)		Hydrophilic aluminium
	e.Tube outside dia.and type	mm	Φ7,inner grooved tube
	f.Coil length x height x width	mm	1380x210x13.37
	g.Number of circuits		2
Indoor air flow		m3/h	580
Indoor sound pressure level		dB(A)	49
Indoor sound power level		dB(A)	53
Indoor unit	Dimension (W x Dx H)(body)	mm	570x570x260
	Packing (W x Dx H)(body)	mm	655x655x290
	Dimension (W x Dx H)(panel)	mm	647x647x50
	Packing (W x Dx H)(panel)	mm	715x715x123
	Net/Gross weight(body)	kg	16/20
	Net/Gross weight	kg	2.5/4.5
Design pressure		MPa	4.2/1.5
Drainage water pipe dia.		mm	ODΦ25
Refrigerant piping	Liquid side/ Gas side	mm	Φ6.35/Φ9.52(1/4"/3/8")
Controller			RG51Q1/BGE
Operation temperature	Cooling	°C	17~32
	Heating	°C	0~30