

| | | | |
|-----------------------------|--------------------------------|---------|------------------------|
| Model | | | LV2MCI-18 |
| Power supply | | V-ph-Hz | 220~240-1-50 |
| Cooling | Capacity | Btu/h | 18000 |
| | Input | W | 102 |
| | Rated current | A | 0,44 |
| Heating | Capacity | Btu/h | 18000 |
| | Input | W | 102 |
| | Rated current | A | 0,44 |
| Indoor fan motor | Model | | YDK37-4P |
| | Qty | | 1 |
| | Output | w | 65/46/32 |
| | Capacitor | uF | 2UF/400-450V |
| | Speed(hi/mi/lo) | r/min | 830/720/660 |
| Indoor coil | a.Number of rows | | 2 |
| | b.Tube pitch(a)x row pitch(b) | mm | 21x13.37 |
| | c.Fin spacing | mm | 1,3 |
| | d.Fin type (code) | | Hydrophilic aluminium |
| | e.Tube outside dia.and type | mm | Φ7, inner groove tube |
| | f.Coil length x height x width | mm | 1370x210x26.74 |
| | g.Number of circuits | | 4 |
| Indoor air flow | | m3/h | 800 |
| Indoor sound pressure level | | dB(A) | 46 |
| Indoor sound power level | | dB(A) | 54 |
| Indoor unit | Dimension (W x Dx H)(body) | mm | 570x570x260 |
| | Packing (W x Dx H)(body) | mm | 655x655x290 |
| | Dimension (W x Dx H)(panel) | mm | 647x647x50 |
| | Packing (W x Dx H)(panel) | mm | 715x715x123 |
| | Net/Gross weight(body) | kg | 18/20.5 |
| | Net/Gross weight | kg | 2.5/4.5 |
| Design pressure | | MPa | 4.2/1.5 |
| Drainage water pipe dia. | | mm | ODΦ25 |
| Refrigerant piping | Liquid side/ Gas side | mm | Φ6.35/Φ12.7(1/4"/1/2") |
| Controller | | | RG51Q1/BGE |
| Operation temperature | Cooling | °C | 17~32 |
| | Heating | °C | 0~30 |